



## New England KM III Static Kernmantle Rescue Rope



**UL Classified to NFPA 1983**

**A superior handling rescue lifeline, New England Ropes KM III static, kernmantle rope features a composite construction of nylon and polyester fibers. KM III has a weight-balanced construction with the sheath and the core each representing 50% of the total weight. The rope is torque-balanced to eliminate any spin during a rappel. The continuous filament polyester sheath is braided over a continuous nylon fiber core. This provides excellent handling and knot-holding characteristics, as well as rugged protection from abrasion and cutting. The polyester sheath provides added protection for ultraviolet light and from chemicals that are harmful to nylon. The polyester sheath also reduces the strength loss and weight gain that occurs when nylon absorbs water.**

Item#	Product	U/M	NFPA	Diameter	Color	Weight
K00120	Lifeline, 3/8", White/Blue, KM III Static, New England	Ft	Light-Use	3/8 inch (9.5mm)	White (Blue)	4.7 lbs (2.1kg) / 100 ft
K05120	Lifeline, 3/8", Orange/Blue, KM III Static, New England	Ft	Light-Use	3/8 inch (9.5mm)	Orange (Blue)	4.7 lbs (2.1kg) / 100 ft
K00140	Lifeline, 7/16", White/Blue, KM III Static, New England	Ft	Light-Use	7/16 inch (11mm)	White (Blue)	5.4 lbs (2.4kg) / 100 ft
K05140	Lifeline 7/16", Orange/Blue, KM III Static, New England	Ft	Light-Use	7/16 inch (11mm)	Orange (Blue)	5.4 lbs (2.4kg) / 100 ft
K00160	Lifeline, 1/2", White/Blue, KM III Static, New England	Ft	General-Use	1/2 inch (12.5mm)	White (Blue)	7 lbs (3.2kg) / 100 ft
K05160	Lifeline, 1/2", Orange/Blue, KM III Static, New England	Ft	General-Use	1/2 inch (12.5mm)	Orange (Blue)	7 lbs (3.2kg) / 100 ft
K01160	Lifeline, 1/2", Red/White, KM III Static, New England	Ft	General-Use	1/2 inch (12.5mm)	Red (White)	7 lbs (3.2kg) / 100 ft
K02160	Lifeline, 1/2", Green/Blue, KM III Static, New England	Ft	General-Use	1/2 inch (12.5mm)	Safety Green (Blue)	7 lbs (3.2kg) / 100 ft
K03160	Lifeline, 1/2", Blue/White, KM III Static, New England	Ft	General-Use	1/2 inch (12.5mm)	Blue (White)	7 lbs (3.2kg) / 100 ft
K04160	Lifeline, 1/2", Black, KM III, New England	Ft	General-Use	1/2 inch (12.5mm)	Black	7 lbs (3.2kg) / 100 ft



**Maritime Provinces**  
**Phone: (902) 468-6060**  
**Fax: (902) 468-9090**  
**Toll Free (800) 667-3030**

**Newfoundland**  
**Phone: (709) 747-3099**  
**Fax: (709) 747-3098**  
**Toll Free (888) 941-6224**



## CMC Rescue Static-Pro™ Lifeline



**UL Classified to NFPA 1983**

**Constructed of 100% high-tenacity polyester fiber, Static-Pro Lifeline is an extremely low stretch, kernmantle rescue lifeline that provides advantages when the need for super low elongation offsets the need for the rope to provide energy absorption in the system. With less than 1% stretch at 300 lbs., Static-Pro is an excellent choice for high lines, long rappels, and many mechanical advantage haul systems. Its low electrical conductivity has advantages when working on towers or charged electrical equipment. The polyester fiber ropes have better resistance to acids than nylon, making Static-Pro an advantage in acidic environments.**

***The Static-Pro Lifelines come in solid colors with a single stripe to prevent confusion with CMC Rescue Lifeline and other solid color kernmantle ropes.***

Item#	Product	U/M	NFPA	Diameter	Color (Stripe)	Weight
281102	Lifeline, 7/16", Blue/White, Static-Pro, Light-Use	Ft	Light-Use	7/16 inch (11.5mm)	Blue (White)	6.5 lbs (2.9kg) / 100 ft
281103	Lifeline, 7/16", Orange/White, Static-Pro, Light-Use	Ft	Light-Use	7/16 inch (11.5mm)	Orange (White)	6.5 lbs (2.9kg) / 100 ft
281109	Lifeline, 7/16", Red/White, Static-Pro, Light-Use	Ft	Light-Use	7/16 inch (11.5mm)	Red (White)	6.5 lbs (2.9kg) / 100 ft
281200	Lifeline, 1/2", White/Blue, Static-Pro, General-Use	Ft	General-Use	1/2 inch (12.5mm)	White (Blue)	8.6 lbs (3.9kg) / 100 ft
281201	Lifeline, 1/2", Orange/White, Static-Pro, General-Use	Ft	General-Use	1/2 inch (12.5mm)	Orange (White)	8.2 lbs (3.9kg) / 100 ft
281202	Lifeline, 1/2", Blue/White, Static-Pro, General-Use	Ft	General-Use	1/2 inch (12.5mm)	Blue (White)	8.2 lbs (3.9kg) / 100 ft
281203	Lifeline, 1/2", Red/White, Static-Pro, General-Use	Ft	General-Use	1/2 inch (12.5mm)	Red (White)	8.2 lbs (3.9kg) / 100 ft
281207	Lifeline, 1/2", Yellow/White, Static-Pro, General-Use	Ft	General-Use	1/2 inch (12.5mm)	Yellow (White)	8.2 lbs (3.9kg) / 100 ft



**Maritime Provinces**  
**Phone: (902) 468-6060**  
**Fax: (902) 468-9090**  
**Toll Free (800) 667-3030**

**Newfoundland**  
**Phone: (709) 747-3099**  
**Fax: (709) 747-3098**  
**Toll Free (888) 941-6224**



### Gibbs Ascenders

Gibbs Ascenders provide excellent performance under the most adverse conditions, gripping on even muddy and icy ropes. Used for years for ascending by cavers, Gibbs are also used by many rescue teams for ratchets in haul systems and in other rope grab applications where a mechanical ascender provides greater efficiency. The Sport models are intended for ascending rope and work well for pack hauling systems for climbers and cavers. The Rescue models have a heavier shell and larger diameter pin for greater strength when used in a litter hauling system. On all models, the bottom of the shell has been modified to provide a curved interface with the rope for greater strength. With the spring loaded models, the spring prevents the ascender from sliding down the rope when the cam is not loaded. All models fit rope from 7/16 to 1/2 in. (11 - 12.5 mm)

**Note:** The breaking strength applies to the unit. The actual Gibbs/rope performance will vary depending on the type, brand, and condition of the rope.

#### Gibbs Spring Kit

Manufactured by Gibbs products and fits all new model Gibbs Ascenders. Replaces the coil spring with cable spring.

### CMC Rescue Rack

UL Classified to NFPA 1983 - General Use

The CMC Rescue Rack offers several innovative features to provide enhanced performance. The "fat" aluminum bars provide excellent control for rescue loads. The bars are center drilled to reduce weight and allow better heat dissipation and have CMC's exceptionally long wearing proprietary finish that we use on our aluminum Rescue 8s. The finish also prevents transfer of material to the rope, common with bare aluminum bars. The Turbo Bar at the top has a tie-off pin on the side. The second bar has a straight slot to help warn the user of a mis-rigged rack. Since the top two bars do most of the work, they are a full one inch in diameter. The next four angled slot bars are 7/8 inch. The stainless steel frame has a welded eye and locking nut. The rack comes assembled, ready for use.



### Petzl I'D Self-Braking Descender

UL Classified to NFPA 1983

Its auto-locking feature combined with a locking position for the handle make the Petzl I'D an excellent descender for working on rope. Additional safety features include an anti-panic function that stops the descent if the handle is pushed too far and an anti-error safety catch that reduces the risk of an accident from the incorrect installation on the rope. Maximum descent distance: 660 ft. (200m).

The Small (345D21) model has a safety clip on the swinging side plate reduces the risk of dropping the device when removed from the rope, such as when passing intermediate anchors.



**Maritime Provinces**  
**Phone: (902) 468-6060**  
**Fax: (902) 468-9090**  
**Toll Free (800) 667-3030**

**Newfoundland**  
**Phone: (709) 747-3099**  
**Fax: (709) 747-3098**  
**Toll Free (888) 941-6224**



**CMC ProSeries Harness Combo**

**UL Classified to NFPA 1983 - Class III**

The ProSeries Harness Combo combines the ProSeries Rescue Harness and ProSeries Chest Harness to make a Class 3, full body harness. The chest harness can be removed allowing the sit harness to be used by itself. If your primary need is a Class 3 harness, but you want the flexibility of also having a sit harness, the combo is a great deal.

Item#	Product	U/M	Size	Waist
203172	Harness Combo, Small, CMC ProSeries	Ea	Small	26-30 in. (66-76cm)
203174	Harness Combo, Regular, CMC ProSeries	Ea	Regular	30-44 in. (76-112cm)
203175	Harness Combo, X-Large, CMC ProSeries	Ea	X-Large	42-46 in. (107-117cm)

**CMC ProSeries Confined Space Rescue Harness**

**UL Classified to NFPA 1983 - Class III and ANSI Z359.1**

More than ever, the very popular CMC ProSeries Confined Space Rescue Harness is the all-around choice for confined space operations, heavy rescue and USAR incidents. The multiple attachment points include an ANSI rated fall arrest point, shoulder lift points, and a front waist D-ring for comfortable rappels. The vest, that keeps the shoulder straps organized to make donning the harness easy, is now made of a new blue mesh with improved breathability. A new hand grip has been added to the back for assisting the wearer out of tight spaces. The harness has a radio pocket and a multi-tool or cell phone pocket. The zippered accessory pocket is ideal for a small gas monitor. Based on the CMC ProSeries design, this harness is exceptionally comfortable, even when used for a shoulder lift. The molded waist padding with the lumbar support and the breathable D3 cloth provide industry leading comfort. The redesigned buckle system and unique CMC Web Keepers provide ease



**Attachment points:** dorsal; front waist; rear waist; sternal; shoulders.

Item#	Product	U/M	Size	Waist	Weight
202162	Harness, Small, Confined Space Rescue, CMC ProSeries	Ea	Small	26-32 in. (66-82cm)	7.89 lbs
202164	Harness, Regular, Confined Space Rescue, CMC ProSeries	Ea	Regular	32-42 in. (82-107cm)	8.01 lbs
202165	Harness, X-Large, Confined Space Rescue, CMC ProSeries	Ea	X-Large	42-48 in. (107-122cm)	8.25 lbs



**Maritime Provinces**  
**Phone: (902) 468-6060**  
**Fax: (902) 468-9090**  
**Toll Free (800) 667-3030**

**Newfoundland**  
**Phone: (709) 747-3099**  
**Fax: (709) 747-3098**  
**Toll Free (888) 941-6224**